

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A computerized method of representing at least one characteristic of a design element on a visual design surface, the method comprising:

(a) using shapes to visually represent design elements on a visual design surface, wherein the design elements are entities of a process or system being designed by a user, and the design elements include a first design element and a second design element;

(b) defining characteristics for the design elements such that each of the design elements is associated with one of the characteristics, wherein the determination of the characteristic associated with each design element is independent of the determination of the characteristics associated with the other design elements, and wherein the characteristic associated with the first design element is different than the characteristic associated with the second design element; ;

(c) associating the characteristics with auras, respectively, each of the auras being a visually perceptible element on the visual design surface that is distinguishable from the other auras, wherein different ones of the characteristics are associated with different auras;

(d) displaying the shape for each design element on the visual design surface with the aura associated with the characteristic associated with that design element, wherein the shapes of the first and second design elements are displayed with different auras; and

(e) automatically moving the shapes of design elements sharing a particular one of the characteristics into an affinity region for the particular characteristic, such that the moved shapes are located in proximity to each other on the visual design surface.

2. (Original) The method of claim 1, wherein the aura comprises a color coded area surrounding the shape.

3. (Original) The method of claim 1, wherein the aura comprises a color coded area adjacent to at least a portion of the shape.

4. (Previously Presented) The method of claim 1, further including:

(f) merging the auras associated with the shapes of design elements in the affinity region for the particular characteristic.

5-6. (Canceled)

7. (Currently Amended) A computerized The method of representing at least one characteristic of a design element on a visual design surface, the method comprising: ~~claim 1,~~ further including

(a) using shapes to visually represent design elements on a visual design surface, wherein the design elements are entities of a process or system being designed by a user, and the design elements include a first design element and a second design element;

(b) defining characteristics for the design elements such that each of the design elements is associated with one of the characteristics, wherein the characteristic associated with the first design element is different than the characteristic associated with the second design element;

(c) associating the characteristics with auras, respectively, each of the auras being a visually perceptible element on the visual design surface that is distinguishable from the other auras, wherein different ones of the characteristics are associated with different auras;

(d) displaying the shape for each design element on the visual design surface with the aura associated with the characteristic associated with that design element, wherein the shapes of the first and second design elements are displayed with different auras; and

(e) automatically moving the shapes of design elements sharing a particular one of the characteristics into an affinity region for the particular characteristic, such that the moved shapes are located in proximity to each other on the visual design surface; and

(f) providing a label for at least one affinity region in a manner that allows a user to change the label in order to change the design elements contained in the affinity region from design elements associated with the particular characteristic to design elements associated with another characteristic.

8. (Previously Presented) The method of claim 1, wherein the characteristics defined in (b) include a use for the design element.

9. (Previously Presented) The method of claim 1, wherein the characteristics defined in (b) include an identification of a namespace.

10. (Previously Presented) The method of claim 1, wherein the characteristics defined in (b) include an identification of an application layer.

11. (Previously Presented) The method of claim 1, wherein the characteristics defined in (b) include an identification of an importance level.

12. (Previously Presented) The method of claim 1, wherein (d) further includes:
associating a particular design element with first and second characteristics; and
displaying the shape for the particular design element on the visual design surface with the auras associated with the first and second characteristics, respectively.

13. (Previously Presented) The method of claim 12, wherein (d) further includes:
associating the particular design element with a third characteristic; and
determining the shape for the particular design element on the visual design surface with the aura associated with the third characteristic.

14-18 (Canceled)

19. (Previously Presented) A computer-readable medium containing computer-executable instructions for performing the steps comprising:

(a) displaying on a visual design surface multiple shapes corresponding to design elements, respectively, the multiple design elements including first and second design elements; and

(b) defining characteristics for the design elements such that each of the design elements is associated with one of the characteristics, the characteristic associated with the first design element being different from the characteristic associated with the second design element;

(c) defining auras for the characteristics, respectively, such that different characteristics have different auras, each of the auras being a visually perceptible element on the visual display surface that is distinguishable from the other auras;

(d) displaying on the visual design surface each of the design element shapes in proximity with the aura generated for the characteristic associated with the design element; and

(e) automatically moving the shapes of design elements sharing a particular one of the characteristics into an affinity region for the particular characteristic, such that the moved shapes are located in proximity to each other on the visual design surface,

wherein (d) visually indicates that the first and second design elements have different characteristics, and

wherein the design elements are entities of a process or system being designed by a user.

20. (Previously Presented) The computer-readable medium of claim 19, wherein (d) comprises displaying the aura around the design element shape.

21. (Canceled)

22. (Previously Presented) The method of claim 1, wherein each of the characteristics defined in (b) comprises one of the following: a particular namespace for the corresponding design element, a particular importance level for the corresponding design element, a particular security requirement for the corresponding design element, and a particular intended use within the process or system for the corresponding design element.

23. (New) The computer-readable medium of claim 19, wherein in step (b) the determination of the characteristic associated with each design element is independent of the determination of the characteristics associated with the other design elements.

24. (New) The method of claim 1, wherein the design elements comprise at least one of the following: business processes, flowchart steps, hosting platforms, and hardware components.

25. (New) The computer-readable medium of claim 19, wherein the design elements comprise at least one of the following: business processes, flowchart steps, hosting platforms, and hardware components.